

Technical Data Timan 3330

Motor	Kubota
Number of cylinders	3
Piston displacement	962
Hp / kW	33 / 24
Cooling system	Water cooling (45°C outdoor temperature)
Gasoline tank	37 L
Transmission	Piston pumps
Wheel motors	x 4 Orbital motors
Speed	28 km/h
Work hydraulics	Gear pumps
Capacity outlet rear	48 L/min (nominal) 180 Bar
Capacity outlet front	48 L/min (nominal) 180 Bar
Oil outlet front	1 double-acting with flowing position 150 Bar
Oil outlet rear	1 double-acting 150 Bar
Lifting arm	Flow position and parallel lift standard
Lifting capacity	150 kg 80 cm from quick change 300 kg at the quick change
Electrical System	12 Volt
Generator	65 Amp
Driving work lights front	x 2 + 2
Rear working light	x 1
Rotating beacon	Standard
13 pole trailer connector	Standard
Radio with Bluetooth and hands-free	Standard
Sound level cabin EU1322/2014 method B	79dB
Passing EU985/2018 running	71dB
Passing EU985/2018 standing	74dB
Sound level cabin at 2.600 rmp.	68 dB
Source strength Lwa ISO 6395:2008	105dB
Weights and Measures	
Acces height	500 mm
Length	2.700 mm
Width	1.130 mm
Height	1.990 mm
Turning radius (internal)	530 mm
Net weight	1.060 kg
Movable weight	1.185 kg