



TECHNICAL DATA

Timan 3330



Technical specifications

Engine	Kubota
Hp / kW	33 / 24
Petrol tank	37 L
Number of cylinders	3
Piston displacement	962
Cooling system	Water cooling (45°C outdoor temperature)
Speed	28 km/h
Transmission	Piston pumps
Wheel motors	4 x Orbital motors
Capacity outlet front	48 l/min (nominal) 180 bar
Capacity outlet rear	48 l/min (nominal) 180 bar
Oil outlet front	1 double-acting with flowing position 150 Bar
Oil outlet rear	1 double-acting 150 Bar
Work hydraulics	Gear pumps
Lifting arm	Flow position and parallel lift standard
Lifting capacity	300 kg at the quick change 150 kg, 80 cm from quick change
Electrical System	12 Volt
Generator	65 Amp
Driving work lights front	2 + 2
Rear working light	1
Rotating beacon	Standard
13 pole trailer connector	Standard
Radio with Bluetooth and hands-free	Standard



Dimensions

Net weight	1.060 Kg
Movable weight	1.185 Kg
Length	2.700 mm
Width	1.130 mm
Height	1.990 mm
Acces height	500 mm
Turning radius (internal)	530 mm
Turning radius (external)	1.670 mm



Noise levels

Sound level cabin EU1322/2014 method B	79 dB
Passing EU985/2018 running	71 dB
Passing EU985/2018 standing	74 dB
Sound level cabin at 2.600 rmp.	68 dB
Source strength Lwa ISO 6395:2008	105 dB



Options

Air conditioning
Sliding windows on the right and left side of the cabin
Air-sprung driver's seat
Camera at the suction mouthpiece
Rear view camera
Reverse warning beeper
Warning lights
LED beacon flash
Reverse headlamp LED
Trailer coupling combination, ball and jaw coupling