

Technical Specifications Timan Tool-Trac 5740

Engine	Kubota
Number of Cylinders	4
Displacement	1,6 L
Hp / kW	57 / 42,5
Cooling	Water cooling (up to 40°C)
Fuel Capacity	58 L
Transmission	Hydrostatic Drive
Wheel Motors	4 Hydraulic Piston Motors
Top Speed	40 km/h
Number of Gears	2
4WD in Low Gear	Constant
Diff. Lock front/rear	Constant
Diff. Lock right/left	Optional 100% lock
Work Hydraulic	2 Gear Pumps
Capacity hydr. Outlet rear	36 L/min (nominal) 210 Bar
Capacity hydr. Outlet front	62 L/min (nominal) 250 Bar (26 kW)
Hydraulic outlet front	1 double acting with lock 250 Bar 2 double acting w/o lock 210 Bar
Hydraulic outlet rear	1 single acting with lock and return 1 double acting with lock and floating pos.
Lifting arm	Floating and parallel: Standard
Lifting capacity	550 kg 60 cm from quick coupling 900 kg at quick coupling
Lifting height	2.500 mm horizontal shovel
System voltage	12 Volt
Alternator	65 Amp
Driving + work light front	2 + 4
Work Light rear	2 stk
Rotorblink	Standard
7-pin trailer connector	Standard
Radio with Bluetooth	Standard
Aircondition	Standard
Dimensions and Weight	
Entry height	430 mm
Length	2.940 mm
Width	1.250 mm
Height	1.980 mm
Turning radius (inside)	830 mm
Weight	Ca. 1.700 kg